

Desktop type duplex thermal printer

UB Series

**High-spec thermal printer capable of double-sided thermal printing.
Depending on the application, you can select the head size on the bottom surface.**

A printer that can print on both sides simultaneously.
Both sides 4 inches type. Surface 4 inches 2 inches back side.
Surface 2 inches 4 inches back side. There are abundant variations of choices depending on the customer's purpose such as 2-inch type on both sides.



If you select the ribbon, you can also print different colors on one side and boasts of design.

Easily manage print contents on the top and bottom sides with a PC

- ✓ Head up when there are few print data such as date.
- ✓ Save ribbon in proportion to data length
- ✓ Various prints reduce bags and film items.
- ✓ Printing in the forward, reverse, vertical, horizontal, and 4 directions is possible.
- ✓ Printing in the forward, reverse, vertical, horizontal, and 4 directions is possible....
- ✓ Printing of various 2D codes and image files such as QR codes.

Specification list

Brand	Shinmei			
Origin	Japan			
Assembling	Japan			
Warranty	Standard 12 months			
Model	CPS-UB44 II	CPS-UB42 II	CPS-UB24 II	CPS-UB22 II
Work size	70~340(W)×110~400(L)			
Printing method	Thermal ribbon thermal transfer method 4 inch head 12dot 1280dot/line 2 inch head 12dot 640dot/line			
Print head	4 inch 12dot×2 groups	4+2 inches 12dot×2 groups		2 inches 12dot×2 groups
Print area	106×200mm(L)×2 groups	106×200mm(L)+53×200mm(L)		53×200mm(L)×2 groups
Printing speed / Number of processed sheets	200 mm / sec 【100 mm / sec ~ 250 mm / sec (change setting possible)】 / 40 sheets / (A 5 size) * 1			

Character type	barcode(2of5[ITF]、JAN[13.8]、2of7[NW7]、3of9[CODE29]、CODE · 128[CODE SUBSET A、B、C]) · OCR · line · CR code · 8 kinds of Win font · vertical and horizontal enlargement (1 to 4 times) · ANK · Chinese character
Print position / character direction	Free setting(In some areas there is a dead zone, and there is a position where printing is impossible.) 0°/90°/180°/270°
External dimensions	590×330×370
Power supply / weight	AC100V · 600W · 50/60Hz · 40kg
option	Editing software · various feeders · various stackers · neutralizer